



Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

Sal- Acid disks GHS Compliant MSDS

SECTION I- PRODUCT AND COMPANY IDENTIFICATION

Product Name: Salicylic- Acid Disks
Recommended Use of Chemical: WART, CORN AND CALLUS REMOVER
Manufacturer: Akron Coating & Adhesives 365 Stanton Ave. Akron Oh 44301
PHONE: 330-724-4716 FAX: 330-724-5923

24 Hour Emergency Information Telephone Number 1-330-329-0098

RECOMMENDED USE OF CHEMICAL: WART, CORN AND CALLUS REMOVER

SECTION 2- HAZARD IDENTIFICATION

WARNING: IRRITANT, CAUSES SKIN IRRITATION



WASH HANDS THOROUGHLY AFTER HANDLING MATERIAL AND BEFORE EATING OR DRINKING.

HMIS (0 TO 4)	
HEALTH	2
FIRE HAZARD	0
REACTIVITY	0

EFFECTS OF EXPOSURE

INHALATION: N/A

SKIN CONTACT: Skin contact may aggravate existing dermatitis

EYE CONTACT: Contact with the eyes would be expected to cause irritation

MEDICAL CONDITIONS PRONE TO AGGRAVATION: Skin contact may aggravate existing dermatitis

PRIMARY ROUTE OF ENTRY: DERMAL

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

Product Composition

(Mixture)			
Chemical Identity CAS or Chemical Name:	CAS Number:	Percent	Hazardous Per 29 CFR 1910.1200:
Salicylic Acid	69-72-7	35%-40%	No
Acrylic Pressure Sensitive Adhesive	N/A	60%-65%	
Polyvinyl Alcohol (CELVOL)	9002-89-5	01%-05%	No



Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

SECTION 4-FIRST AID MEASURES

Always seek professional medical attention after first aid measures are provided.

Emergency First Aid procedures

Eyes: Immediately flush with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention.

Skin: Immediately flush with water for at least 15 minutes. Get medical attention. If clothing comes in contact with the product, the clothing should be removed immediately and should be laundered before re-use. Components of product can be absorbed through the skin resulting in toxic effects.

Ingestion: Potential for aspiration if swallowed. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward.

Inhalation: N/A

Most Important Symptoms/side effects

Acute exposure

Inhalation If inhaled may cause irritation to the upper respiratory tract. Any irritation would be transient with no permanent damage expected. Inhalation of high concentrations may cause headache, dizziness, drowsiness, and nausea.

Skin: Skin contact may produce mild irritation consisting of transient redness. This irritant effect would not result in permanent damage.

Eye: Contact with the eyes would be expected to cause irritation consisting of reversible redness, swelling, tearing, and mucous discharge to the conjunctiva.

Ingestion: No data is available on the effects of acute ingestion of this product. However, ingestion may cause gastrointestinal discomfort with any or all of the following symptoms: nausea, lethargy or diarrhea.

Chronic exposure

Inhalation Prolonged or repeated inhalation of this product may cause allergic respiratory sensitization.

Skin: Since liquid material may be absorbed through the skin, prolonged or repeated contact may result in absorption of harmful amounts. Prolonged or repeated skin contact may cause dermatitis.

Repeated or prolonged skin contact may also cause some individuals to develop skin rash or other skin complications due to allergic skin sensitization.

Ingestion: There are no known or reported effects from chronic exposure.

SECTION 5-FIREFIGHTING MEASURES

Flash Point: 157 ° C

Extinguishing Media: Dry chemical powder

Extinguishing equipment that is not appropriate: N/A



Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

Unusual Fire and Explosion Hazard: N/A

Protective equipment and precautions for firefighters: Use a NIOSH approved positive pressure self-contained breathing apparatus when this material is involved in a fire.

Special protective actions for firefighters: Use water to cool containers exposed to fire.

SECTION 6- ACCIDENTAL RELEASE MEASURES

Personal protection recommended:

Respiratory Protection: N/A

Skin and Eye Protection: Protective clothing recommended

Other: N/A

Emergency procedures and cleanup procedures: Confine to a small area. Place in appropriately marked container for disposal.

Steps to be taken in case material is released or spilled

Air Release: N/A

Water Release: Notify all downstream water users of possible contamination. Divert water flow around spill if possible and safe to do so. If unable to divert, create an overflow dam to contain material. Continue to handle as described in land spill.

Land Spill: Confine to a small area. Place in appropriately marked container for disposal.

Waste Disposal Method: See Section 13 for disposal information.

SECTION 7- HANDLING AND STORAGE

Handling Precautions: N/A

General hygiene practices: Wash hands thoroughly after handling material and before eating or drinking.

Handling incompatible chemicals: N/A

Appropriate Storage Conditions: Store in a secure area to prevent damage

Incompatible materials for storage: Product may deteriorate with heat

Incompatible materials for transport: N/A

SECTION 8-EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Chemical Name</i>	<i>Exposure Standards</i>
N/A	N/A
N/A	N/A

Respiratory Protection: N/A

Ventilation: N/A



Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

Skin and Eye Protection: Protective clothing recommended

Other: N/A

Hygienic Practices: Wash hands thoroughly after handling material and before eating or drinking.

SECTION 9-PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale Yellow	
Odor: Mild sour	Upper/Lower Flammability: N/A
Odor Threshold: N/A	Vapor Pressure(@ 25⁰ C): N/A
pH: N/A	Vapor Density: 4.8
Melting Point: 158°C (316° F) Freezing Point: N/A	Relative Density : N/A
Initial Boiling Point: N/A	Solubility: N/A
Flash Point: 157°C	Partition Coefficient: N-Octanol/Water: N/A
Evaporation Rate: N/A	Auto ignition Temperature: N/A
Flammability (Solid, Gas) : N/A	Decomposition Temperature: N/A
Viscosity: N/A	

SECTION 10- STABILITY AND REACTIVITY

Chemical Stability: N/A

Possibility of hazardous Reactions: N/A

Conditions to avoid: N/A

Incompatible Materials: Strong oxidizers, mineral acids

Hazardous decomposition products: N/A

Organic peroxides, pyrophoric, unstable (reactive) or water reactive hazards: N/A

Hazardous Polymerization: N/A

Reactivity: N/A

Shelf life: 3 years

SECTION 11-TOXICOLOGY INFORMATION

Warning Statements and Warning Properties

May cause skin, eye and respiratory irritation. Prolonged or repeated skin contact may cause dermatitis.

Acute Symptoms/Signs of exposure

Eyes: Contact with the eyes would be expected to cause irritation consisting of reversible redness, swelling, tearing, and mucous discharge to the conjunctiva.

Skin: Skin contact may produce mild irritation consisting of transient redness. This irritant effect would not result in permanent damage.

Ingestion: No data is available on the effects of acute ingestion of this product. However, ingestion may cause gastrointestinal discomfort with any or all of the following symptoms: nausea, lethargy or diarrhea.



Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

Inhalation: If inhaled, may cause irritation to the upper respiratory tract. Any irritation would be transient with no permanent damage expected. Inhalation of high concentrations may cause headache, dizziness, drowsiness, and nausea.

Chronic Effects:

Inhalation: Prolonged or repeated inhalation of this product may cause allergic respiratory sensitization.

Skin: Since liquid material may be absorbed through the skin, prolonged or repeated contact may result in absorption of harmful amounts. Prolonged or repeated skin contact may cause dermatitis.

Sensitization: Repeated or prolonged skin contact may also cause some individuals to develop skin rash or other skin complications due to allergic skin sensitization.

Numerical Measures of Toxicity:

Acute Target organ Toxicity	May cause skin, eye, mucous membrane, and respiratory tract irritation. Inhalation of high concentrations of vapors may cause dizziness or drowsiness.
Skin Corrosion/Irritation	This product may cause dermatitis upon prolonged or repeated skin contact.
Serious Eye Damage/Irritation	No Data Available
Respiratory Or Skin Sensitization	No Data Available
Germ Cell Mutagenicity	No Data Available
Carcinogenicity	No Data Available
Reproductive Toxicity	No Data Available
Aspiration Hazard	No Data Available
Aquatic Toxicity:	No Data Available
Chronic Target Organ Toxicity:	This product may cause dermatitis upon prolonged or repeated skin contact.

None of the ingredients of this product are listed on NTP (National Toxicology Program), IARC (International Agency for Research on Cancer, or found to be potential carcinogen by OSHA.



**MATERIAL
SAFETY DATA**

Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

SECTION 12-ECOLOGICAL INFORMATION

Ecotoxicity: No Data Available

Persistence and degradability: No Data Available

Bio-accumulative potential: No Data Available

Mobility in soil: No Data Available

Other adverse effects: No Data Available

Environmental Data

There are no environmental data available for this product or its components.

SECTION 13-DISPOSAL CONSIDERATION

Material Waste: Check with all applicable local, regional, and national laws and regulations. Local regulations may be more stringent than regional or national regulations. Use a licensed chemical waste disposal firm for proper disposal.

Packaging and Containers: Disposal must be in accordance with applicable federal, state /provincial, and/or local regulations.

SECTION 14-TRANSPORTATION INFORMATION

US DOT

UN/NA: N/A

PROPER SHIPPING NAME: Not regulated for non-bulk quantities

TRANSPORT HAZARD CLASS: N/A

PACKING GROUP: N/A

MARINE POLLUTANT: NO

SPECIAL PRECAUTIONS: N/A

SECTION 15- REGULATORY INFORMATION

CHEMICAL NAME	TSCA
N/A	N/A
N/A	N/A

FOR ADDITIONAL ASSISTANCE CONTACT AKRON COATING & ADHESIVES PHONE: 330-724-4716



**MATERIAL
SAFETY DATA**

Akron Coating & Adhesives
365 Stanton Ave.
Akron, Ohio 44301
Phone: 330-724-4716 FAX: 330-724-5923

SECTION 16- OTHER INFORMATION

Current issue date: April 14, 2015 Rev. 2

Disclaimer: *The information provided on this MSDS is the best estimate of technically qualified individuals but may not be based on direct toxicology testing or experience in emergency situations. It must be used by or under the direct supervision of technically qualified individuals (as defined in 40cfr 710.2). Because safety standards and regulations are subject to change and because AKRON COATING & ADHESIVES has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. AKRON COATING & ADHESIVES makes no warranty, expressed or implied, including (without limitation) warranties with respect to the completeness or continuing accuracy of the information contained herein or with respect to fitness for any particular use. IF THIS MSDS IS MORE THAN THREE YEARS OLD, YOU SHOULD CONTACT AKRON COATING & ADHESIVES AT 330-724-4716 TO MAKE SURE THAT THIS SHEET IS CURRENT.*

Consult plant procedures in the event of a spill or leak for handling and environmental information

THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200. THIS PRODUCT MAY BE CONSIDERED TO BE A HAZARDOUS CHEMICAL UNDER THAT STANDARD. (REFER TO THE OSHA CLASSIFICATION IN SEC I.) THIS INFORMATION IS REQUIRED TO BE DISCLOSED FOR SAFETY IN THE WORKPLACE. THE EXPOSURE TO THE COMMUNITY, IF ANY, IS QUITE DIFFERENT.