

Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Good Sense Regular Scent Nail Polish Remover

Item Number: HB00531

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Davion Inc.	Emergency Telephone Number 703-527-3887 or 800-424-9300
Address (Number, Street, City, State, and ZIP Code) 29-75 Riverside Avenue	Telephone Number for Information 973-485-0793
Newark, New Jersey 07104	Date Prepared August 27, 2008 Date Revised September 20, 2010
Signature of Preparer (optional)	

Section II - Hazardous Ingredients/Identity Information

Hazardous Components: (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Acetone (CAS No. 67-64-1)	1000 ppm (TWA) 2400mg/m ³	500ppm(TWA)	A4-Currently no evidence to suggest a concern for carcinogenicity	60-80%

Ingredients:

Water, Glycerin, Fragrance, Yellow 11 (CI 47000)

Emergency overview:

Use according to label directions.

Section III - Physical/Chemical Characteristics

Appearance	Product	Pale Yellow liquid with a fragrant smell.	
	Acetone	Clear, colorless, volatile liquid.	
Boiling Point	56.2 °C (133 °F)	Specific Gravity (H ₂ O = 1)	0.889

Vapor Pressure (mm Hg)	0.823	Melting Point	-95.3° C (-139°F)
Vapor Density (AIR = 1)	2.0	Evaporation Rate (Butyl Acetate = 1)	>7
Solubility in Water	Miscible in all proportions	% Volatiles by volume @ 21C (70F):	100

Section IV - Fire and Explosion Hazard Data

Flammable Limits	Auto ignition Temperature	Flash Point (Method Used)	LEL	UEL
Flammable Liquid and Vapor NFPA Fire Rating; 3	465°C (869° F)	-4° F (-20°C) (Closed Cup)	2.5%	12.8%

Extinguishing Media:

Use alcohol resistant foam, dry chemical powder, carbon dioxide or water spray

Special Fire Fighting Procedures

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or the positive pressure mode.

Unusual Fire and Explosion Hazards

Upon decomposition, this product may emit carbon dioxide, carbon monoxide and/ or low molecular weight hydrocarbons.

Section V - Reactivity Data

Stability		
Stable	Unstable	Conditions to Avoid
Stable under normal ambient temperature 21°C (70°F)	N/A	Heat, sparks, open flame and vapor accumulation.
Incompatibility (<i>Materials to Avoid</i>):	Strong oxidizing agents, strong acid and strong bases.	
Hazardous Decomposition or Byproducts:	Carbon dioxide and carbon monoxide	
Hazardous Polymerization:		
May Occur	Will Not Occur	Conditions to Avoid
N/A	√	N/A

Section VI - Health Hazard Data

Route(s) of Entry:			
Inhalation: Inhalation of vapors irritates the respiratory tract. May cause coughing, dizziness, dullness, and headache.	Eyes: Liquid or vapor may cause irritation.	Ingestion: Harmful if swallowed of larger amount. May produce abdominal pain, nausea and vomiting	Skin: Prolonged and repeated skin contact may cause redness, pain, drying and cracking of the skin.

Signs and Symptoms of Exposure

Eye irritation, and if ingested – vomiting or diarrhea

Medical Conditions Generally Aggravated by Exposure:

Use of alcoholic beverages enhances toxic effect. Exposure may increase the toxic potential of chlorinated hydrocarbons such as chloroform and trichloroethane.

Section VII – Emergency and First Aid Procedures**Inhalation:**

Remove source of contamination or move victim to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Eye: Flush eyes with plenty of water for at least 20 minutes. For contact lens users, remove lens and flush with water. If irritation persists, seek medical attention.

Ingestion:

Do not induce vomiting. Contact Poison Control Center and seek medical attention.

Skin Contact:

Flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. If irritation continues, get medical attention.

Section VIII - Precautions for Safe Handling and Use**Steps to Be Taken in Case Material is Released or Spilled:**

Evacuate personnel to a safe area. Remove all sources of ignition. Contain and collect spillage with non-combustible absorbent material (e.g. sand, earth) and place in a compatible labeled waste container for disposal in accordance with local, state and federal regulations. Prevent discharge to open waters.

Precautions to Be taken in Handling and Storing

Keep the container tightly closed. Store in a cool, dry and well-ventilated area.

Other Precautions

Keep out of the reach of children.

Section IX - Control Measures/Personal Protection**Engineering Controls**

Normal room ventilation is usually adequate to keep employee exposure under below the Airborne Exposure Limits. Local Exhaust is recommended if possible.

Respiratory Protection

If the exposure limit is exceeded and engineering control is not feasible, a half -face organic vapor respirator may be worn for up to ten times the exposure limit. A full face organic vapor respirator may be worn up to 50 times the exposure limit.

For emergencies, or instances where the exposure limit is not known, use a full-face piece positive pressure respirator.

Eye/Face Protection

Use chemical safety goggles and or full face shield where splashing is possible. Maintain Eye wash fountain and quick-drench facilities in work area.

Skin protection:

Wear gloves, lab coat, apron or coveralls, as appropriate to prevent skin contact.

Other Protective Clothing or Equipment

Container should be bonded and grounded for transfer to avoid static sparks. Storage and use area should be no smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation.

Work/Hygienic Practices

Standard safe working and hygienic practices.

Section X – Toxicological Information

No information available for product. Product contains mainly Acetone.
Acetone (67-64-1)

Acute effect:

Oral rat LD50: 5800 mg/kg; Inhalation rat LC50: 50,100mg/m3; Irritation eye rabbit, Standard Draize, 20 mg severe; Investigated as a tumorigen, mutagen, and reproductive effector.

Chronic effect:

Carcinogenicity: ACGIH A4- Not Classifiable as a Human Carcinogen
Target Organs: Acetone can target the respiratory system, eyes, kidneys, and hematology.
May depress central nervous system and may cause dermatitis.

Section XI – Ecological Information**Environmental Fate:**

When released into the soil, this material is expected to readily biodegrade or evaporated. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by photolysis. Or readily removed from the atmosphere by wet deposition.

Section XII – Disposal Information

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Section XIII – Transportation Information**Domestic (Land, D.O.T.)**

Proper Shipping Name: ACETONE

Hazard Class: 3

UN/NA: UN1090

Packing Group: II

(Information reported for product size 188L)

International (Water, I.M.O.)

Proper Shipping Name: ACETONE

Hazard Class: 3

UN/NA: UN1090

Packing Group: II

(Information reported for product size 188L)

Section XIV – Regulatory Information

Acetone, a component of this product, is on the TSCA inventory and CERCLA/SARA. RCRA waste number U002 (Ignitable waste)

**Chemical Inventory Status - Part 1 **

Ingredient	TSCA	EC	Japan	Australia
Acetone (67-64-1)	Yes	Yes	Yes	Yes

**Chemical Inventory Status - Part 2 **

	-Canada-			
Ingredient	Korea	DSL	NDSL	Phil.
Acetone (67-64-1)	Yes	Yes	No	Yes

**Federal, State & International Regulations - Part 1 **

-SARA 302-

-SARA 313-

Ingredient	RQ	TPQ	List	Chemical Catg.
Acetone (67-64-1)	No	No	Yes	No

Federal, State & International Regulations - Part 2\ -----

Ingredient	CERCLA	-RCRA-	-TSCA-
Acetone (67-64-1)	5000	261.33 U002	8(d) No

Chemical Weapons Convention: No TSCA 12(b): Yes CDTA: Yes
 SARA 311/312: Acute: Yes Chronic: No Fire: Yes Pressure: No
 Reactivity: No (Pure / Liquid)

Section XV – Other Information

Disclaimer of expressed and Implied Warranties

The information and recommendations contained in the Material Safety Data Sheet (MSDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

HABA, Division of Davion, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will HABA, Division of Davion, be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or any other nature, are made by HABA Division of Davion hereunder with respect to information or the product to which the information refers. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.